


EPA GROUND WATER INVESTIGATION

San Mateo Creek Basin Uranium Legacy Site


January 12, 2017








UPPER SAN MATEO CREEK BASIN







SAN MATEO MINE



ARROYO


Photo from USFS






CONCEPTUAL SITE GROUND WATER MODEL

Generalized Cross Section Through San Mateo Creek Basin



CONCEPTUAL SITE GROUND WATER MODEL



MULTI-PHASED GROUND WATER INVESTIGATION

Phase 1

Alluvial Aquifer 2012 – 2016

Phase 2

Bedrock & Alluvial Aquifers 2015 – 2017



Phase 3

Develop Conceptual Site Model 2016 - 2018

PHASE 1 COMPLETED

EPA Phase 1 Ground Water Report

- Completed in August 2016
- Released to stakeholders in September 2016

Key components include:

- Summary of historical studies on uranium mining impacts
- Field investigation
- Findings and Conclusions

HISTORICAL STUDIES ON URANIUM MINING IMPACTS


- 1975 EPA study
 - Ground water contamination discovered
 - Sources mine water discharge and tailing seepage
 - Perennial flows created in creeks/arroyos
- 1981 and 1986 New Mexico studies
 - Alluvial ground water exceeds standards
 - Mine water discharge rapidly infiltrates and saturates alluvium



1975 – Ambrosia Lake Area

IMPACT OF MINE WATER DISCHARGE OPERATIONS

- Dewatered underground workings
- Discharged billions of gallons of mine water to creeks and arroyos
- Water infiltrated into ground
- Increased amount of ground water in alluvial sediments and bedrock
- Changed quality of ground water




Draft – For Discussion Purposes Only Not to Scale

SUMMARY OF HISTORIC MINE WATER DISCHARGE QUALITY

Comparison to Alluvial Background Water Quality

Contaminant	1981 Mine Water Discharge Ambrosia Lake Area	1981 Mine Water Discharge San Mateo Area	1978-80 San Mateo Creek Upland Alluvial GW (Background)	
Gross Alpha (pCi/L)	580	1,100	2.5 – 15.0	
Uranium (mg/L)	2.4	0.080	0.005 - 0.010	
Selenium (mg/L)	0.410	0.040	0.005 - 0.005	
Molybdenum (mg/L)	0.79	0.32	0.005 - 0.010	
Chloride (mg/L)	90	10	3 – 8	
Sulfate (mg/L)	837	205	5-20	
Total Dissolved Solid (mg/L)	1,690	520	125 – 300	


New Mexico 1981 and 1986 Reports




MINE WATER DISCHARGE

Artificially
Created
Surface Flows in
Creeks
and Arroyos








SUMMARY OF CONCLUSIONS

Phase 1 Report

- Attempt to Characterize Alluvial Background had Mixed Results
 - Lack of Natural Saturation in Many Areas Investigated
- Alluvial Water Quality Varies Across Basin
 - Good quality upgradient of mines and mills
 - ✓ Meets standards
 - Poor quality downgradient of mines and mills
 - ✓ Exceeds standards
 - ✓ Similar to mine discharge water quality in some areas
- Mine Discharge Water Draining Through and Out of Alluvium



Alluvium

SMC Alluvial Ground Water

Rio San Jose Alluvial Ground Water

EPA Background
Well


Well Downgradient to Legacy Mines


16 Uranium (ppb)

610 Total Dissolved Solids (ppm)

MASSIVE SATURATION AND DRAIN DOWN OF ALLUVIUM

- Caused by mine water discharges
- Water levels in central part of basin raised and dropped
 OVER 50 FEET
- Drain down not observed near Homestake





Alluvium


SMC Alluvial Ground Water


Rio San Jose Alluvial Ground Water


EPAMonitoringWell - 2014


1960 or Older Well

Dry BoreholeDrilled in2014/2015











HISTORIC WATER LEVELS

HOMESTAKE NPL SITE



From Homestake Mining Company **SELENIUM CONCENTRATION** 12 MAP 914 920 West Edge of Alluvial Aquifer O ND --LEGEND--SE CONCENTRATIONS, mg/l -0.1 - SE CONTOUR Upgradient PLEASANT > SE 95% UTL* VALLEY **GRP Area** MURRAY > SE 95% UTL* ND O Well Location * Based on 1995-2004 Data T.12N

HOMESTAKE NPL SITE



CONTAMINANT MASS LOADINGS FROM MINES

1	8	Section 35	Mine, Ar	nbrosi	a Lake	, NM			2		
2		Mass of Uranium,	Molybdenum	, & Selen	ium disch	arged from 1960	to 1976 before NPDES t	reatment required			
3	LOWER M	INE WATER	DISCHA	RGE R	ATE	50 22				+	
5		Discharge Period	Discharg e Rate GPM	minute s per day	million gallon s per day (MGD)	AVG COC concentrati on in mine effluent (MG/L)	Formula: Ibs/day = dose X flow x 8.34 lb/gal	AVG POUNDS PER DAY (lbs/day)	AVG POUNDS PER YEAR	16 YEAR TOTAL POUNDS DISCHARGED	16 YEAR TOTAL TONS DISCHARGED
-	URANIUM	1960-1976	850	1,440	1.22	5.25	(5.25 MG/L) X (1.22 MGD) X 8.34 lb/gal	53.59	19561.39	312982.19	156.49
-	MOLYBDENUM	1960-1976	850	1,440	1.22	1.91	(1.91MG/L) X (1.22 MGD) X 8.34 lb/gal	19.50	7116.62	113865.90	56.93
9	SELENIUM	1960-1976	850	1,440	1.22	0.02	(0.02 MG/L) X (1.22 MGD) X 8.34 lb/gal	0.20	74.52	1192.31	0.60
1 2 3	HIGHER N	INE WAT	FR DISC	HARG	FRΔ	TE					
14	THO TEXT	Discharge Period	Discharg e Rate GPM	minute s per day	million gallon s per day (MGD)	AVG COC concentrati on in mine effluent (MG/L)	Formula: lbs/day = dose X flow x 8.34 lb/gal	AVG POUNDS PER DAY (lbs/day)	AVG POUNDS PER YEAR	16 YEAR TOTAL POUNDS DISCHARGED	16 YEAR TOTAL TONS DISCHARGED
-	URANIUM	1960-1976	2,618	1,440	3.77	5.25	(5.25 MG/L) X (3.77 MGD) X 8.34 lb/gal	165.07	60249.07	963985.13	481.99
6 7 8	MOLYBDENUM	1960-1976	2,618	1,440	3.77	1.91	(1.91MG/L) X (3.77 MGD) X 8.34 lb/gal	60.05	21919.19	350706.97	175.35
	SELENIUM	1960-1976	2,618	1,440	3.77	0.02	(0.02 MG/L) X (3.77 MGD) X 8.34 lb/gal	0.63	229.52	3672.32	1.84